

## Waste Recycle Pull Outs

Product features:

- Bottom mount.
- Full extension (500 mm).
- Soft close.
- Easy installation with only 4 screws.
- Door mount brackets and clip on handle included in the kit.

Waste Bins:

- Recyclable, non-toxic material.
- Resistant to low & high temperatures.
- Does not deform.
- Integrated handles for easy removal.
- Optional lids and charcoal filters available.



Door-mount bracket Features: Patented system; 3-way adjustability for alignment of the cabinet door: height (+/-2mm), Side (+/-3mm) and depth (+/-4mm), easy installation with only two screws; suitable for standard style doors and five piece doors as well.

## Fly Moon



An innovative and unique space saving corner unit. The shelves can be pulled-out independently, trays are designed to increase storage surface, height adjustable shaft, easy to install. The mechanism is a patented system and can be easily fixed in on one side of the cabinet, non-slip melamine surface, for frame and frameless cabinets, load capacity 44 lbs per shelf, minimum door opening 85°, height of the shelf rail 70 mm (2-3/4"). Two colors are available: white shelves with chrome wire and maple shelves with champagne wire. Several sizes available including 13 5/8"!

Shelf kit contents: 2 pull-out pivoting shelves; metal plates for connection; assembly instruction. Mechanism kit contents: mechanism with height adjustable shaft; brackets and extension pipe; assembly instruction. Soft close version is available.

## Smart Corner

Smart Corner unit requires a minimum door opening of 17". Easy assembly, full extension and soft closing system, open in one movement, automatically allows free access to the rear baskets, non-slip surface, for frameless cabinets, load capacity: back shelves 44 lbs (20 kg) - front shelves 22 lbs (10 kg). Inside height min. 22-3/8". Not reversible. This is the ultimate blind corner solution.

Kit contents: base corner unit system, set of 4 baskets (2 front and 2 rear), full extension soft close slides (400 mm), adjustable door mounting bracket, assembly instructions. The door opening angle can be adjusted in three different positions.

